

HMIS RATING	
HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PROTECTION	B
<small>Hazard Index</small> 4 - SEVERE HAZARD 3 - SERIOUS HAZARD 2 - MODERATE HAZARD 1 - SLIGHT HAZARD 0 - MINIMAL HAZARD	

CAUTION: DO NOT TAKE INTERNALLY

Use only with adequate ventilation. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection. (NIOSH/MSHA approved) Any person using a respirator must be properly trained in respirator use. Close container after each use. Avoid contact with eyes and skin. Dispose of empty containers in accordance to all applicable regulations.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Give conscious victim 1 to 2 glasses of water and get medical attention immediately.

Wet material will not burn. Dried films of this material can burn, and can be extinguished by foam, CO2, or water spray.

TRU MARK

Athletic Field Marker

SWITCHBACK

CHEAP SEATS

WHITE

P.O. BOX 706, NORFOLK, NE 68702-0706
1-800-553-6275 Fax: 707-276-1061
www.AthleticFieldMarker.com - TruMarkAthletic@gmail.com

NET CONTENTS: 5 US GALLONS (18.93 L)

MIXING INSTRUCTIONS

Mix thoroughly before dilution.
Dilute paint up to 2:1 with water.
Stir thoroughly before using.

SURFACE PREPARATION

Preparation of the ground is not necessary however, do not apply on a rain soaked or frosty field.

APPLICATION INSTRUCTIONS

Use a field paint-marking machine for application and follow the manufacturer's instructions. Material will dry in approximately one hour, depending on conditions.

CLEAN UP INSTRUCTIONS

Clean all equipment immediately after painting with warm soapy water.

LIMITATIONS

Apply according to equipment manufacturers instructions. Do not store in freezing temperatures. Avoid application under rain and snow conditions or when frost or dew are present.

DOT SHIPPING NAME: Not regulated.

Coating VOC less than 100 g/l (0.83 lb/gallon)



**DO NOT
FREEZE**

BATCH NUMBER