

HMIS RATING	
HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PROTECTION	B
<small>Hazard Index</small> 4 - SEVERE HAZARD 3 - SERIOUS HAZARD 2 - MODERATE HAZARD 1 - SLIGHT HAZARD 0 - MINIMAL HAZARD	

CAUTION: DO NOT TAKE INTERNALLY

Use only with adequate ventilation. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection. (NIOSH/MSHA approved) Any person using a respirator must be properly trained in respirator use. Close container after each use. Avoid contact with eyes and skin. Dispose of empty containers in accordance to all applicable regulations.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Give conscious victim 1 to 2 glasses of water and get medical attention immediately.

Wet material will not burn. Dried films of this material can burn, and can be extinguished by foam, CO2, or water spray.

TRU MARK

Athletic Field Marker

TRAILBLAZER

SOLAR TRAIL

**SYNTHETIC TURF PAINT
MARKING PAINT FOR PERMANENT APPLICATIONS**

WHITE

P.O. BOX 706, NORFOLK, NE 68702-0706
1-800-553-6275 Fax 707-276-1061
www.AthleticFieldMarker.com - TruMarkAthletic@gmail.com

NET CONTENTS: 5 US GALLONS (18.93 L)

MIXING INSTRUCTIONS

Product is supplied ready to use, thinning is not required. Product should be stirred prior to use to eliminate any settling or phase separation which may occur upon storage or shipping.

SURFACE PREPARATION

Synthetic grass fibers should be upright and not lying flat. Apply over a clean, dry turf.

APPLICATION INSTRUCTIONS

Use an airless sprayer with tip sizes 314 to 317 with pressure at the tip at 2500-3000 psi. With spray tip approximately 12 inches from the surface apply a light and uniform coating on the synthetic turf. Spray evenly in one direction and return by applying a second coat over the same line. The paint will dry to touch in approximately one hour, and dry completely in 6-8 hours, depending on conditions. Coverage is 900 linear feet of 4 inch line per gallon (300 ft²/gallon). Special colors also available.

CLEAN UP INSTRUCTIONS

Clean all equipment immediately after painting with warm soapy water.

LIMITATIONS

Apply according to equipment manufacturers instructions. Do not store in freezing temperatures. Avoid application under rain and snow conditions or when frost or dew are present.

DOT SHIPPING NAME: Not regulated.

Coating VOC less than 250 g/l (2.09 lb/gallon)



**DO NOT
FREEZE**

BATCH NUMBER