

Revised 12/2007

U. S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME

Technical Coatings Corporation

EMERGENCY TELEPHONE NO.

770-740-8123

ADDRESS (Number, Street, City, State and ZIP Code)

3085 Trotter Parkway, Alpharetta, GA 30201

CHEMICAL NAME AND SYNONYMS

N/A

TRADE NAME AND SYNONYMS

Stripe X

CHEMICAL FAMILY

Paint

FORMULA

White and Colors

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES & SOLVENTS		%	TLV	ALLOYS AND METALLIC COATINGS		%	TLV
PIGMENTS				BASE METAL			
CATALYST				ALLOYS			
VEHICLE				METALLIC COATINGS			
SOLVENTS				FILLER METAL			
OTHERS				OTHERS			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES						%	TLV

SECTION III - PHYSICAL DATA

BOILING POINT	212 F	SPECIFIC GRAVITY	1.05
VAPOR PRESSURE		PERCENT. VOLATILE	
VAPOR DENSITY	Heavier than Air	BY VOLUME	83
SOLUBILITY IN WATER	100%	EVAPORATION RATE	
APPEARANCE AND ODOR	Various Colors	WGT PER GALLON	8.76

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used)	200F	FLAMMABLE LIMITS	LEV 5.5	UAL
EXTINGUISHING MEDIA	Dry Chemical			
SPECIAL FIRE FIGHTING PROCEDURES	Keep Materials from heat, spark, and open flame			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Water should be used to cool containers			

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Remove person to fresh air

Skin Contact: Wash with soap and water

Eye Contact: Flush eyes with water for at least 15 minutes, contact Physician

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATIBILITY (Material to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition and ventilate vapors. Absorb with an inert material.

WASTE DISPOSAL METHOD

Dispose in accordance with Federal, State, and Local Regulations

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Adequate ventilation is required. Use a respirator in confined areas, approved by U.S. Bureau of Mines.

VENTILATION	LOCAL EXHAUST	Provide sufficient ventilation to keep vapor concentration below T.V. and L.E.L.	SPECIAL
	MECHANICAL (General)		OTHER

PROTECTIVE GLOVES	Requires for prolonged contact	OTHER PROTECTIVE EQUIPMENT
-------------------	--------------------------------	----------------------------

EYE PROTECTION	Use eye protection sufficient to prevent eye contact
----------------	--

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Close containers after each use. Avoid damage to containers to prevent spills. Keep material from heat, sparks and open flames.

OTHER PRECAUTIONS